

## REFRESH

**FlexCoat**<sup>™</sup> FlexCoat is a urethane top dressing which may be applied to any rubber safety surface. Our FlexCoat urethane coating rebinds the rubber granules, improving the product's useful life. FlexCoat also rejuvenates and refreshes surface colors. FlexCoat is recommended as a preventative maintenance application. To ensure longevity, it is recommended that a FlexCoat be applied every two years. It is recommended to pressure wash and power blow surface as needed before FlexCoat is applied.



## REPAIR

**FlexGrout**<sup>™</sup> This newly engineered grouting compound repairs and strengthens rubberized surfacing systems, and has been tested to withstand even the most extreme conditions. Tired of repairs to loose and granulated rubber in high-wear areas such as underneath swings or at slide exits? Installing a new pad and just want to make sure you don't have to deal with that inevitable hassle? FlexGrout is the perfect option for use in high-wear areas.

**FlexFix**<sup>™</sup> Finding holes in your previously applied rubber surface? FlexGround can quickly and easily repair minor and major damage. Small repairs can be made in various designs and colors (triangles, circles, happy faces etc) in order to create the appearance that the repaired area was part of the original design.



## RETOP

**FlexTop**<sup>™</sup> FlexTop is the solution for widespread and severely damaged rubber. It consists of reapplying the EPDM or TPV top surface (and cushioning where needed). FlexTop can be applied as 1.5" over existing wear layer, or can be accomplished by removing the existing color layer, freshening the cushion and then installing a new 1/2" color wear layer. Either method works to conceal any age and maintain or improve critical fall.

